Town of Orangetown

Bureau of Fire Prevention

20 Greenbush Road Orangeburg, New York 10962 Ph(845)365-0204fax(845)365-0241

HOW TO PREPARE FOR YOUR FIRE SAFETY INSPECTION MULTIPLE RESIDENCE

- 1. Smoke detectors must be located in each bedroom/sleeping room.
- 2. Smoke detectors must be in each hallway on each level within the dwelling. And in each public hallway on each level.
- 3. Carbon Monoxide alarms must be installed within each dwelling unit on each level. And in each public hallway on each level(combination carbon monoxide/smoke alarms are permitted if they are listed for that use)
- 4. Exterior fire escapes must be in good working order, tested annually, and free of corrosion. The landing beneath the fire escape must be kept clear and unobstructed.
- 5. Fire extinguishers where required must be inspected and retagged annually.
- 6. Fire sprinkler systems must be inspected/tested annually, (Orangetown inspection form must be completed by sprinkler contractor)
- 7. Fire lanes must be maintained at all times, ie: signs/striping in place, and clear of obstructions.
- 8. Where a monitored fire alarm system (NFPA 72 compliant) with direct connection to 44-Control(Rockland County Fire Dispatch) is present, the system must be inspected/tested quarterly and a copy of the report forwarded to this office.
- 9. All hallways, stairwells and exit doors must be kept clear of storage.
- 10. Exit signs must be illuminated at all times and have a backup power supply of not less then 90 minutes.
- 11. Emergency lights must be functioning when tested and have a backup power supply of not less then 90 minutes.
- 12. Open flame cooking is not permitted within 10 feet of any structure. In addition the storage of propane is not permitted within any structure.
- 13. The use of slidebolts, or deadbolts with an interior keylock is not permitted on a public exit door.